

SpecBond, Inc.

3015 W. Cornelia Ave. Chicago, IL 60018 Phone: 773-967-0138 Fax: 312-268-5448 www.SpecBond.com

# PRODUCT DATA SHEET SB908

# Description

**SB908** is a matte surface finish PVC film tape with a total thickness of 6 mils. Used for color coding; lane marking and safety coding to meet OSHA requirements; decorating and striping on vehicles, boats, sporting equipment, etc.; masking of printed circuit boards; harness and pipe wrapping and duct and joint sealing.

**SB907** is available in 16 colors: Yellow, White, Black, Clear, Red, Orange, Dark Blue, Medium Blue, Sky Blue, Gray, Purple, Dark Brown, Medium Brown, Emerald Green, Kelly Green and Light Green.

### Construction



# Feature and Benefits

**SB907** has a long shelf-life and "write-on" capability. It provides a very effective vapor and moisture barrier. It is highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalis and corrosive chemicals. It provides good abrasion, impact and rupture resistance.

Conforms to Government Spec. AA-1689B, Type II

<b>I ypical Properties</b> (not to be used for specification purposes)			
Property	Test Method	Value (US)	Value (Metric)
Total Thickness	PSTC-33	6.0 mils	0.15 mm
180°Peel Adhesion	PSTC-101	22 oz/inch	6.0 N/25 mm
Tensile Strength	PSTC- 131	256 oz/inch	28 N/10 mm
Elongation	ASTM D3575	150% at break	150% at break
Temp Range		-20°F-176° F	-29°C-80°C

#### Typical Properties (not to be used for specification purposes)

For maximum adhesion, bonding surfaces should be clean, dry and free from grease and oils. The firmer the application pressure and the greater the contact area, the stronger the bond.

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business.